



Charakteristika

top



- Innovative concept of decorative air curtain based on a recessed model to be installed free-hanging.
- Sklandų priekinį skydelį galima pritaikyti naudojant logotipus, apšvietimą, užrašus arba saugos ir informacinius signalus, atsižvelgiant į kliento reikalavimus.
- Self-supporting casing construction made of galvanized steel plate painted in grey RAL9006. Kitos spalvos yra prieinamos pagal pageidavimą.
- Inlet and Outlet inbuilt in the same grid painted in white RAL9016. Kitos spalvos yra prieinamos pagal pageidavimą.
- Anoduoto aliuminio išleidimo mentės, orlaivio formos.
- Mažo triukšmo sukami kryžminio srauto ventiliatoriai, varomi 2 greičių išorinio rotoriaus varikliu.
- "P" tipo su vandeniu šildomu šildymo elementu ir integruota reguliacija ON/OFF arba trys stadijos 0-10V proporcingo vožtuvo. „E“ tipo su ekranuotais elektriniais elementais, trijų stadijų su integruotu reguliavimu. „A“ tipo be šildymo, tik oras.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
 - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
 - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.

Specifikacija

50Hz

Modelis	(m ³ /h)	(m)
TOP 1000 A	3.5	
TOP 1500 A	3.5	
TOP 2000 A	3.5	

Modelis	(m ³ /h)	(kW)	(m)
TOP 1000 E	3.5		
TOP 1500 E	3.5		
TOP 2000 E	3.5		

Modelis	(m ³ /h)	(kW)	(m)
TOP 1000 P86	3.5		
TOP 1500 P86	3.5		
TOP 2000 P86	3.5		
TOP 1000 P64	3.5		
TOP 1500 P64	3.5		
TOP 2000 P64	3.5		

Matmenys

